

## C238 2U MicroATX ULTRA COOL SERVER CHASSIS

webpage updated on July 24, 2012



The era of MicroATX constructed Dual-core and Quad-Core CPU platform has been the mainstream nowadays, the fast and stable server system is also presented by this model of design, the major feature of this brand new design is the depth of this chassis has 380mm only, it supports the most cost effective and stable quality, combines with two intake 80mm fans at front side, comes with totally 4 drive bay with the chassis configuration, fits all standard MicroATX 9.6"x9.6" motherboard form factor and standard PS2 power supply, meets regular server system application.



- \* Total drive bay: 2 x 5.25" CD and 2 x 3.5" HDD bay
- \* HDD bay with anti-vibration function supported
- \* equipped two USB 2.0 port
- \* two [Sunon EE80251B1-000C-G99](#) 80mmx25mm intake fans with air filter at front bezel
- \* MB: MicroATX(9.6"x9.6")-Mini-ITX(6.7"x6.7")
- \* support PS2 power supply with [80mm fan version](#) (max. psu depth: 140mm)
- \* support 4 slot Low Profile expansion cards (max. 175mm long)
- \* standard paint: black
- \* [Branded server chassis model \(with build-in fans\) global 3 years warranty](#)
- \* chassis dimension: 19" x 2U x 380mm (14.96" deep)
- \* package: NW 5 KGM, GW 7 KGM, 1.72 CUFT (56x51x17cm, single box packed)

Model# :	C238B	2U black MicroATX ultra cool server chassis
Option 1 :	PSU	PS2 power supply with PFC and with <a href="#">80mm fan version</a> (support psu depth 140mm maximum)
Option 2-0 :	<a href="#">NJ-600</a>	600mm 2-layer 3-travel universal slide rail , full travel extension up to 1100mm deep (part# is 1 pair)
Option 2-1 :	<a href="#">1234U-RMK</a>	1234U rear mounting kit (part# is 1 pair)
Option 3 :	<a href="#">135TO225BK</a>	1x3.5" HDD space to 2x2.5" aluminum heatsink-like bracket
Option 4-0 :	<a href="#">2525TO3HDBK</a>	2x5.25" ODD space to 3x3.5" bracket
Option 4-1 :	<a href="#">425IN525</a>	1x5.25" ODD space to 4x2.5" hotswap mobile rack module
Option 4-2 :	<a href="#">335IN2525</a>	2x5.25" ODD space to 3x3.5" hotswap mobile rack module