RACK-220G

2U 6-slot Full-size Rackmount Chassis



Features

- ♦ RoHS compliant design
- ◆ Two USB ports on the front panel
- ◆ Two, 8 cm cooling fans with replaceable fan filter
- ♦ One 5.25" and one 3.5" drive bay
- ♦ One 3.5" internal hard drive bay
- ◆ Lockable door prevents unauthorized access

Specifications

♦ Construction	Heavy duty metal
♦ SBC Form Factor	Full-size, slot CPU card
♦ Drive Bays	1 x 5.25" 1 x 3.5" 1 x 3.5" HDD (internal)
♦ Cooling Fans	2 x 8 cm
♦ I/O Ports	2 x USB
♦ Expansion Slots	6 slots
♦ Indicators	Power, HDD
♦ Buttons	Power switch, reset button
♦ Operating Temperature	0°C~50°C
◆ Operation Humidity	10% ~ 90%
♦ Color	W:White / B:Black
♦ Weight (Net/ Gross)	8.2 kg / 12.4 kg
♦ Dimensions (DxWxH)	487.5 mm x 431 mm x 88 mm


Ordering Information

Part No.	Description
RACK-220G [/A130A	2U 6-slot Full-size Rackmount Chassis for PICMG 1.0 SBC, (Black/ White), 2 x 8cm fan, with ACE-A130A-R10 (300W ATX model), RoHS
RACK-220G C ATX/A130A	2U microATX motherboard Rackmount Chassis, (Black/ White), 2 x 8cm fan, with ACE-A130A-R10 (300W ATX model), RoHS

C Color Code: B-Black W-White

Full-size card can not be installed in chassis, because of the limitation of height.

Dimensions (measurement units: millimeter)



Selection Guide

Model No.	SBC Type	PSU Type	Color Options
RACK-220G C	PICMG 1.0	PS/2	black / white
RACK-220G C ATX	microATX MB	PS/2	black / white

Backplane Options

Model No. SBC Type PCI	PCI	ISA	PCle			PSU	
Model No.	SBC Type	FCI	ISA	x1	х4	x16	Connector
PCI-5SDA-RS	PICMG 1.0	L2+R2	0	0	0	0	AT/ATX
PCI-5SD5-RS	PICMG 1.0	L2+R2	0	0	0	0	AT
PCI-5SD6-RS	PICMG 1.0	L2+R2	0	0	0	0	ATX
PCI-6SD-RS	PICMG 1.0	L1+R1	L1+R1	0	0	0	ATX

Power Supply Options

Туре	Model No.	Watt
ATX	ACE-925AP-U-RS	250W
	ACE-925AL-RS	300W
ATX	ACE-A130A-R10	300W
	ACE-A140A-S-R10	400W

RACK-220G can support single PS/2 PSU. For more models of IEI PSU, please refer to section 7 or visit www.ieiworld.com.